



The SB 515-PD and SB 515-AS are both active Sub-Woofer designed to complement AEX Systems' range of speaker solutions. The SB 515-AS features an additional AirStream wireless module allowing for easy installations where the running and laying of audio cable is prohibitive.

Both the SB 515-PD and SB 515-AS feature an in-built all digital 150W amplifier. The inbuilt amplifier is governed by carefully tuned DSP, providing just enough punch to fill up the low end of the frequency curve without being too intrusive when installed in F&B outlets, retail outlets, malls or even a hotel lobby.

- Suitable for applications where a full-range high quality sound is required
- 5" Sub-woofer driver with inbuilt DSP controlled 150W all Digital Amplifier
- The SB 515-AS features a zero latency, zero dropout AirStream module for wireless deployment
- The SB 515-PD is integrated with a line matching transformer suitable for receiving 70 V / 100 V line distributed speaker system as well as 0dB Balanced audio.
- Small form factor and aesthetically pleasing design makes the unit easy to conceal



SB 515-PD



SB 515-AS

## Technical Specifications

	SB 515-PD	SB 515-AS
Frequency Response (-10dB)	50Hz - 300Hz	50Hz - 300Hz
Nominal Power (W)	80W	80W
Maximum Power (W)	160W	160W
Sensitivity (dB) 1W@1m	82dB	82dB
Audio Input (dB)	0dB	N/A
Input Impedance ( $\Omega$ )	10k	N/A
Wireless	N/A	AirStream
Speaker Component	5" Subwoofer	5" Subwoofer
Speaker Enclosure	MDF Wooden Enclosure	MDF Wooden Enclosure
Dimensions (WxDxH)	210 x 270 x 230 mm	210 x 270 x 230 mm
Weight	6.5kg	6.5kg

