



The Network Paging Console for the VEB Series is a state of the art touchscreen based paging console unit. It allows the user to operate the unit as well as select the zones via a user friendly GUI. From the GUI, the operator will be able to make zone selections individually. The unit has a gooseneck stalk microphone with LED indicator for live announcements.

Being a network enabled console, the unit can be connected or relocated anywhere within the project without hassle - simply by connecting to the LAN's datapoint.

- Network Paging Console for VEB-CF Series
- Touchscreen interface
- User-friendly GUI for zone selection
- Individual zone selection
- Gooseneck stalk microphone for live announcements
- Network-enabled for easy connection or relocation within the project
- Connectivity via LAN's datapoint



VEB 45-CF

Technical Specification

	VEB 45-CF
Port Interface	RJ45 10/100 Mbps Ethernet TCP/IP Connectivity
Graphic Display	10 inch touch screen, resolution 1920 x 1080 pixels
Microphone	Removable gooseneck with ring LED Unidirectional microphone with windshield
Chime	4 Tone Ascending and 4 Tone Descending. (User customisable)
Power Supply	12 Vdc, 2 A
Power Consumption	3.5W (idle, screen off), 5W (paging), 6W (paging with speaker)
Audio Input	Condenser, 1 Vrms unbalanced
Audio Output	VectusNET PCM Uncompressed Audio
Monitor Speaker	8Ω 1W 1" speaker
Frequency Response	20Hz – 18kHz
Signal to Noise Ratio	>90dB @ 1KHz
Network Interface	RJ45, 10/100 Mbps Ethernet TCP/IP
Network Protocol	VectusNET
Operation Temperature	0°C – 40°C
Operation Humidity	Less than 90% Relative Humidity
Features	Text streaming Volume control Message BGM Status system User / Password for logging Events logs Sound recording Reporting
Paging	Unlimited
Accessories	Power Adapter (DC 12V/2A), Microphone Windshield
Material & Finish	ABS Black, Steel Metal Stand, Black
Dimensions	245 x 53 x 158 mm (W x H x D) (Mic base), 310mm (Goose neck Mic)
Weight	1.2 kg