



The GD 8 is designed for use in outdoor garden applications where the loudspeaker unit is tasked to evenly cover a large area without compromising on the clarity of the system. The full range garden loudspeaker effortlessly provides sound quality and performance, may it be public announcement or background music playback. The unit utilises a dual cone dynamic 166 mm loudspeaker component which has been treated for waterproofing properties. The loudspeaker component is enclosed in a compact HIPS enclosure to withstand harsh outdoor weather conditions, rated to IP65. The unit comes with a built-in audio line matching transformer for both 100 V / 70 V line distributed speaker systems, rated at 30 W.

- Delivers clear, natural speech and gentle background music through a wide-band driver tuned for even, consistent coverage.
- Fully weatherproof to IP65, ready for permanent outdoor mounting and regular wash-down.
- Even 360° coverage spreads sound smoothly and consistently across the listening area.
- 100 V line taps: 30 W, 15 W, 7.5 W; 70 V line taps: 15 W, 7.5 W, 3.8 W.
- Discreet moulded ABS enclosure finished in black grey resists moisture and impact while sitting light and unobtrusive in the ceiling or on the wall.
- Compact Ø268 × 320 mm body, 1.5 kg, easy to mount and position.
- Designed for hotel gardens, resort grounds, theme parks, outdoor dining and landscaped public spaces.



GD 8

Technical Specification

	GD 8
Rated Input	100 V : 30 W (30 - 15 - 7.5 W) 70 V : 15 W (15 - 7.5 - 3.8 W)
Rated Impedance	0.3kΩ, 0.7kΩ, 1.3kΩ
Maximum Power	45 W
Frequency Response	80 Hz - 18 kHz
Sensitivity 1W @ 1m	91 / 106 dB
Coverage Angle (1kHz, -6dB)	360 deg.
Speaker Component	166mm Dual cone loudspeaker component, waterproof treated
Safety	Acc. to EN 60065
Dust & Water Protection	IP65 (acc. to IEC 529)
Material & Finish	Top cover and base: ABS, black grey Speaker panel: ABS, black grey Legs: ABS, black grey
Dimensions	Dia. 268 x 320 mm
Weight	1.5 kg