



Introducing the HC Series HiFi 8inch, the epitome of audio excellence in our HiFi In-Ceiling/In-Wall Speaker category. This series/model name represents an impeccable fusion of high-fidelity sound and seamless integration, setting a new benchmark for superior audio quality. Immerse yourself in a refined auditory experience, discreetly embedded in your ceiling or wall. Elevate your home audio setup with the HC Series HiFi 8inch, where sophisticated design harmonizes with uncompromising sound, delivering an immersive listening encounter that redefines expectations in the HiFi In-Ceiling/In-Wall Speaker category.

- Reproduces music with genuine hi-fi fidelity, pairing a dedicated woofer and tweeter for crisp, detailed highs.
- HC 852, 100 V line taps: 50 W, 25 W, 12.5 W.
- HC 853, 100 V line taps: 50 W, 25 W, 12.5 W.
- Discreet moulded ABS enclosure resists moisture and impact while sitting light and unobtrusive in the ceiling or on the wall.
- HC 852, Ø286 × 108 mm, cut-out Ø248 mm, 2.5 kg.
- HC 853, 363 × 263 × 108 mm, cut-out 322 × 222 mm, 2.7 kg.
- Specified for hotels, restaurants, retail stores, boutiques, lounges and hospitality interiors.



HC 852



HC 853



HC 852 | 2-Way HiFi In-Ceiling Speaker

HC 853 | 2-Way HiFi In-Wall Speaker

Technical Specification

	HC 852	HC 853
Rated Input (RMS)	80W	80W
Peak Power Handling	160W	160W
Power Taps (100V)	50W, 25W, 12.5W	50W, 25W, 12.5W
Rated Impedance	0.2k Ω , 0.4k Ω , 0.8k Ω / 8 Ω	0.2k Ω , 0.4k Ω , 0.8k Ω / 8 Ω
Frequency Response	65Hz - 19kHz	65Hz - 19kHz
Frequency Range (-10 dB)	45Hz - 20kHz	45Hz - 20kHz
Sensitivity (1W/1m)	88dB	88dB
Maximum Peak SPL	110dB (Calculated)	110dB (Calculated)
Coverage Angle	120	120 x 110
Speaker Component	8" Kevlar Woofer + 0.76" Pivoting Silk Dome Tweeter	8" Kevlar Woofer + 0.76" Pivoting Silk Dome Tweeter
Tweeter EQ Control	+2dB / -2dB	+2dB / -2dB
Safety	EN IEC 62368-1	EN IEC 62368-1
Material & Finish	Enclosure: ABS, Grille: Steel	Enclosure: ABS, Grille: Steel
Connectors	Spring Clip Terminals	Spring Clip Terminals
Cutout Dimension	Ø 248 mm	322 x 222 mm
Dimensions	Ø 286 x 108 mm	363 x 263 x 108 mm
Weight	2.5 KG	2.7 KG