



The VH Series is the high powered outdoor column speaker range that is suitable for high ambient noise and wide coverage application. With its high power and sensitivity, it is commonly used on the outdoor fields, stadiums, halls and arenas. The column speakers are designed with 6" speaker drivers aligned together on a single baffled board

to produce uncompromised speech reproduction and music playback. The column speakers are constructed die-casted and extruded aluminum for durability and aesthetic appeal. All models are supplied with matching transformer to cater for both 70V and 100V line. The VH Series consists of three models: VH 680, VH 6100, and VH 6120.

- Full-range column drivers project speech with high intelligibility, holding clarity even across large, echo-prone spaces.
- Fully weatherproof to IP65, ready for permanent outdoor mounting and regular wash-down.
- VH 680, 100 V line taps: 80 W; 70 V line taps: 40 W.
- VH 6100, 100 V line taps: 100 W; 70 V line taps: 50 W.
- VH 6120, 100 V line taps: 120 W; 70 V line taps: 60 W.
- Die-cast aluminium construction finished in white, set behind a steel grille, shrugs off sun, salt, moisture and years of demanding outdoor service.
- VH 680, 225 × 950 × 120 mm (W × H × D), 11 kg.
- VH 6100, 225 × 1170 × 120 mm (W × H × D), 13 kg.
- VH 6120, 225 × 1385 × 120 mm (W × H × D), 15.2 kg.
- A natural fit for houses of worship, transport terminals, atriums, sports halls and covered walkways.



Technical Specification

	VH 680	VH 6100	VH 6120
Rated Input	100V : 80W 70V : 40W	100V : 100W 70V : 50W	100V : 120W 70V : 60W
Rated Impedance	0.1kΩ	0.1kΩ	0.08kΩ
Frequency Response	90 Hz ~ 16 kHz	90 Hz ~ 16 kHz	90 Hz ~ 16 kHz
Sensitivity 1W @ 1m	110 dB	111 dB	112 dB
Speaker Component	166 mm Full-range x 4nos.	166 mm Full-range x 5nos.	166 mm Full-range x 6nos.
Dust & Water Protection	IP65 (acc. to IEC 529)	IP65 (acc. to IEC 529)	IP65 (acc. to IEC 529)
Material & Finish	Enclosure: Aluminum, white Grille: Treated Steel, white Mounting bracket: Metal, white	Enclosure: Aluminum, white Grille: Treated Steel, white Mounting bracket: Metal, white	Enclosure: Aluminum, white Grille: Treated Steel, white Mounting bracket: Metal, white
Accessory	Mounting Bracket	Mounting Bracket	Mounting Bracket
Dimensions	225 x 950 x 120 mm (W x H x D)	225 x 1170 x 120 mm (W x H x D)	225 x 1385 x 120 mm (W x H x D)
Weight	11 kg	13 kg	15.2 kg

